




MOBILE

Air & Power Rentals

a division of Resolute Industrial

THE PREMIER PROVIDER OF HVAC & POWER RENTALS





We're available
24/7

from our strategically located,
fully stocked warehouses
with expanded service
across **the entire
U.S. and Canada.**

MOBILE AIR & POWER RENTALS HAS BEEN A LEADER IN HVAC & POWER RENTAL SOLUTIONS SINCE 1989.

Mobile Air & Power Rentals is the premier HVAC and power solutions provider in North America. Not only are we available 24/7, but we have the equipment, personnel, and know-how to solve your temporary equipment needs quickly and professionally.

Rental equipment is the most logical solution to short or long-term climate control and power needs. Our solutions are designed to provide temporary relief in planned or emergency situations. We pride ourselves on providing high-quality, dependable, and efficient equipment for any application. Our turnkey services are what truly set us apart from other rental houses. From the moment you call, our experienced team is ready to help. We size the equipment you need, install, and service it until your rental ends. Our equipment is utilized in a variety of demanding and critical areas, such as hospitals,

commercial space construction site, schools, computer/server rooms, and more. The reason we have such high confidence in our equipment is our extensive, complete, repeatable, and documented preventative maintenance program that verifies unit performance prior to leaving our warehouse.

From portable heat and cooling solutions to power rentals, we have the equipment you need. Our rental air and water-cooled chillers range from 5 to 1000 tons. Our rental air conditioners range from 1 to 100 tons. Our rental heat fleet consists of indirect fired, direct fired and electric heaters ranging up to 4.5 million BTU units. With the addition of our new power division we now offer rental generators up to 2000kw, along with all the power distribution and accessories you need to complete a setup.

BEYOND CHILL IN EVERY SITUATION

Mobile Air & Power Rentals offers cooling systems and services for temporary and permanent sites of all sizes, in all settings. From emergency and portable cooling equipment rentals to long-term solutions, the combined team provides around-the-clock, customized design service and direct delivery to customers across the nation.

THE COMBINED STRENGTHS OF THE MOBILE AIR TEAM INCLUDE:

- An expanded service area
- Easier access to strategically placed, fully stocked warehouses
- A broader network of sales and distribution representatives
- Increased responsiveness in urgent and emergency situations
- A greater selection of equipment and accessory options for rental and permanent placement

TAILORED COOLING FOR ANY INDUSTRY

From industrial facilities to highly sensitive computer server rooms, every customer site has unique cooling requirements. Our team of experts evaluates each site, identifying specific needs and recommending a customized cooling, ventilation, and/or dehumidification solution.

Among the industries and facilities we serve are:

- Commercial buildings
- Healthcare facilities
- Schools and university campuses
- General contractors
- Industrial and manufacturing plants
- Painting and coating facilities
- Food processing plants
- Agricultural and horticultural complexes
- Power plants and energy companies
- Governments installations
- Events & Entertainment

THE PERFECT TOOL TO KEEP IT COOL

Prescribing the right equipment and configuration for a specific application results in efficient, economical cooling.

The Mobile Air & Power Rentals team is known for providing effective, targeted solutions, including:

- Mechanical contracting
- Partial or whole-building cooling
- Temporary cooling for building renovations
- Computer server and technology equipment room cooling (continuous or emergency and night/weekend applications)
- Spot-cooling for employees and machinery in harsh plant environments
- Indoor humidity controls
- Spot and whole-building ventilation in manufacturing and agricultural settings
- Emergency and temporary portable cooling

WATER COOLED

PORTABLE UNITS

SPOT COOLING SOLUTIONS

A quick and easy solution for your emergency and temporary cooling needs, delivered direct to your building. Able to roll through any standard door. Simple to install, with many options to help with venting warm condenser and cold evaporator air.



1 TON RENTAL AIR CONDITIONER



1.5 TON RENTAL AIR CONDITIONER

Manufacturer	Ocean Air	Ocean Air
Control	Programmable	Programmable
Cooling Capacity	12,000 Btu/h	18,000 Btu/h
Voltage Requirement	1 Phase, 115V	1 Phase, 115V
Total Power Consumption	0.92 kW	1.3 kW
Current Consumption	8.1 amps	11.3 amps
Recommended Fuse Size	15 amps	15 amps
NEMA Plug Configuration	L6 - 20p	L6 - 20p
Voltage	120	120
Fan Type	Centrifugal	Centrifugal
Max. Air Flow - high/low	400 CFM	600 CFM
Max. External Static Pressure	0.15 IWG	0.25 IWG
Max Water Flow (GPM)	0.45 GPM	0.66 GPM
Compressor		
Dimensions	20.125 x 13 x 31.5 in	24.25 x 13 x 37.5 in
Refrigerant		
Net Weight/Shipping Weight	110/130 lb	150/170 lb
Power Cord Gauge	14 AWG (3-core)	14 AWG (3-core)
Power Cord Length	5 ft	5 ft
Condensate Pump at 10' Head	Pump	Pump
Operating Conditions	65°-105°F	65°-105°F
Max. Equivalent Duct Length	30 ft	25 ft

WATER COOLED

PORTABLE UNITS



2 TON RENTAL AIR CONDITIONER



3 TON RENTAL AIR CONDITIONER



5 TON RENTAL AIR CONDITIONER

Manufacturer	Ocean Air	Ocean Air	Ocean Air
Control	Programmable	Programmable	Programmable
Cooling Capacity	23,950 Btu/h	36,000 Btu/h	60,100 Btu/h
Voltage Requirement	1 Phase, 208/230V	1 Phase, 208/230V	3 Phase 208/230V
Total Power Consumption	2.2 kW	2.6 kW	4.8 kW
Current Consumption	9.9 amps	12.0 amps	24/17/6
Recommended Fuse Size	20 amps	20 amps	15 amps
NEMA Plug Configuration	L6 - 20p	L6 - 20p	7765c
Voltage	240	240	208 - 230 1 Phase 208 - 230 3 Phase 480 3 Phase
Fan Type	Centrifugal	Centrifugal	Centrifugal
Max. Air Flow - high/low	810 CFM	1310 CFM	1950 CFM
Max. External Static Pressure	0.25 IWG	0.25 IWG	0.5 IWG
Max Water Flow (GPM)	0.93 GPM	1.32 GPM	3.30 GPM
Compressor			
Dimensions	24.25 x 13 x 37.5 in	28.25 x 18 x 50.25 in	28.25 x 39 x 52.5 in
Refrigerant			
Net Weight/Shipping Weight	160/180 lb	240/270 lb	520/560 lb
Power Cord Gauge	14 AWG (3-core)	8 AWG (3-core)	6 AWG (4-core)
Power Cord Length	5 ft	5 ft	5 ft
Condensate Pump at 10' Head	Pump	Pump	Pump
Operating Conditions	65°-105°F	65°-105°F	65°-105°F
Max. Equivalent Duct Length	50 ft	50 ft	100 ft

AIR COOLED PORTABLE UNITS

SPOT COOLING SOLUTIONS

A quick and easy solution for your emergency and temporary cooling needs, delivered direct to your building. Able to roll through any standard door. Simple to install, with many options to help with venting warm condenser and cold evaporator air.



**1 TON
RENTAL AIR
CONDITIONER**

**1.5 TON
RENTAL AIR
CONDITIONER**

**2 TON
RENTAL AIR
CONDITIONER**

Manufacturer	AmeriCool	AmeriCool	AmeriCool
Model	WPC-3000	WPC-4000	WPC-5000
Tons	1	1.4	1.8
BTU	13,200	16,800	21,000
Evaporator CFM	405/345 CFM	470/400 CFM	560/465 CFM
Condenser CFM/GPM	305 CFM @ 64°F	1250/1120 CFM	1380/1190 CFM
Operating range	64°-113°F	64°-113°F	64°-113°F
Refr type/weight	R-410a / 28.9 oz	R-410a / 35.2 oz	R-410a / 37 oz
Condens removal	3 Gallon Tank	3 Gallon Tank	3 Gallon Tank
Condensate pump available	N/A	Yes	Yes
Evap Max duct	10'	10'	10'
Max condenser duct length	25'	25'	25'
T-stat range	64°-86°F	64°-86°F	64°-86°F
Spot cool range	32°-86°F	32°-86°F	32°-86°F
Power	115 VAC	115 VAC	208/230V 1 ph
Power Connection	5-15 P	5-20 P	CS8365C
Amps FLA	12 A	15.5 A	11.1 A
Circuit Size	15 A	20 A	15 A
Length	26.4"	27"	27"
Width	20.6"	21"	21"
Height	41"	41"	41"
Weight	185 lbs	185 lbs	196 lbs
Max DB	N/A	N/A	N/A

AIR COOLED PORTABLE UNITS



**2.5 TON
RENTAL AIR
CONDITIONER**

**3 TON
RENTAL AIR
CONDITIONER**

**5 TON
RENTAL AIR
CONDITIONER**

**7.5 TON
RENTAL AIR
CONDITIONER**

**12 TON
RENTAL AIR
CONDITIONER**

Manufacturer	AmeriCool	AmeriCool	AmeriCool	AmeriCool	AmeriCool
Model	WPC-7000	WPC-9000	WPC-15000	WPC-23000	WPC-12RT
Tons	2.4	3.1	5.1	7.6	12
BTU	29,000	37,000	61,000	92,000	144,400
Evaporator CFM	741/635 CFM	882/776 CFM	2000/1870 CFM	2890 CFM	2000/4000 CFM
Condenser CFM/GPM	1560 CFM	1660 CFM	3600 CFM	4250 CFM	7200 CFM
Operating range	64°-113°F	64°-113°F	64°-113°F	64°-113°F	64°-113°F
Refr type/weight	R-410a / 44.4 oz	R-410a / 61 oz	R-410a / 112 oz	R-410a / 141 oz	R-410a / 278 oz
Condens removal	3 Gallon Tank	3 Gallon Tank	Pump	Pump	Pump/Drain
Condensate pump available	Yes	Yes	N/A	N/A	Yes
Evap Max duct	10'	10'	10'	10'	50' each
Max condenser duct length	25'	25'	25'	25'	50'
T-stat range	64°-86°F	64°-86°F	64°-86°F	64°-86°F	64°-86°F
Spot cool range	32°-86°F	32°-86°F	32°-86°F	32°-86°F	32°-86°F
Power	208/230V 1 ph	208/230V 1 ph	208/230V 1 ph	208/230V 1 ph	460V 3 ph
Power Connection	CS8365C	CS8365C	CS8365C	CS8365C	CAMLOCK
Amps FLA	15.1 A	20 A	32 A	17.2 A	27 A
Circuit Size	20 A	30 A	50 A	30 A	35 A
Length	29"	52"	29"	52"	75"
Width	22"	29"	52"	29"	34.5"
Height	47"	60"	60"	60"	71"
Weight	216 lbs	254 lbs	661 lbs	761 lbs	1,168 lbs
Max DB	N/A	N/A	N/A	N/A	N/A

AIR COOLED

AIR CONDITIONERS

SPOT COOLING SOLUTIONS

A quick and easy solution for your emergency and temporary cooling needs, delivered direct to your building. Able to roll through any standard door. Simple to install, with many options to help with venting warm condenser and cold evaporator air.



**5 TON
RENTAL AIR
CONDITIONER**




**12 TO
RENTAL AIR
CONDITIONER**

	AmeriCool	Custom
Manufacturer	AmeriCool	Custom
Model	WPC-5RT	Stealth 12
Tons	5	12
BTU	71,000	144,000
CFM	1,998	4050
Operating temp range	64°- 113°F	64°-113°F
Refr type	R-410A	R-410A
Evap duct Supply	1x20"	2x14"
Evap duct Return	1x20"	2x14"
Con duct size	1x20"	N/A
Blower	5hp	35hp
Heat Capacity	N/A	N/A
Power	480V 3 ph	230/460 V 3 ph
Power Connections	CS8365C	Camlock
Length	62.2"	61"
Width	30.5"	43"
Height	58.7"	64"
Weight (lbs)	761 lbs	1,250 lbs
Mounted	Casters	Casters

AIR COOLED

PORTABLE UNITS



**15 TON
RENTAL AIR
CONDITIONER**



**25 TON
RENTAL AIR
CONDITIONER**

Dunham Bush	York
15T	Series 20
15	25
180,000	310,700
5000	6,600
64°-113°F	0°-120°F
R-410A	R-410A
1X20"	2x20"
1X20"	4x20"
N/A	N/A
N/A	15hp
21 kW	N/A
480V 3 ph	460V 3 ph
Camlock	Camlock
96"	12'
66"	8' 5"
96"	5'
4,000 lbs	4,534 lbs
Skid	Skid

AIR COOLED

PORTABLE UNITS



**25 TON
RENTAL AIR
CONDITIONER**



**30 TON VERTICAL
RENTAL AIR
CONDITIONER**

	Trane	American Event Services
Manufacturer	Trane	American Event Services
Model	Voyager TCD300	WhisperKool 2D
Tons	25	30
BTU	300,000	386,746
CFM	10,000	9,500
Operating temp range	32°-100°F	N/A
Refr type	R-410A	R-410A
Evap supply duct	2X20"	3x20"
Evap return duct	2X20"	3x20"
Blower	N/A	10hp
Heat Capacity	*36 kW	72 kW
Power	480v 3ph	480V 3 ph
Connections	Cam-Lock	Cam-Lock
Length	91"	95"
Width	128"	47"
Height	64"	86"
Weight	4,050 lbs	3,507 lbs
Mounted	Skid	Skid

AIR COOLED

PORTABLE UNITS



**30 TON
RENTAL AIR
CONDITIONER**



**50 TON
RENTAL AIR
CONDITIONER**



**50 TON
RENTAL AIR
CONDITIONER**

	Dunham Bush	Smart Family	Daikin
Manufacturer	Dunham Bush	Smart Family	Daikin
Model	30T	SACP46A-HS	Maverick II
Tons	30	40	50
BTU	370,000	470,000	587,722
CFM	8160	6,400-12,000	19000
Operating temp range	64°-113°F	30°-110°F	64°-113°F
Refr type	R-410A	R-410A	R-410A
Evap supply duct	2X20"	2x20"	3X20"
Evap return duct	2X20"	2x20"	4X20"
Blower	N/A	10hp	40hp
Heat Capacity	45 kW	*75 kW	N/A
Power	480V 3 ph	460V 3 ph	460V 3 ph
Connections	Cam-Lock	Cam-Lock	Cam-Lock
Length	86"	78"	233"
Width	96"	88"	102"
Height	99"	98"	89"
Weight	5,000 lbs	4,620 lbs	7,000 lbs
Mounted	Skid	Skid	Skid

***HEAT IS AVAILABLE ONLY ON SOME UNITS**

WE ARE THE CHAMPIONS OF CHILLERS



80 TON RENTAL AIR CONDITIONER



80 TON RENTAL AIR CONDITIONER



80 TON RENTAL AIR CONDITIONER

Manufacturer	Smart Family	Caps	Caterpillar
Model	SACP80A-HS	PPKH-80TD	Stealth 80
Tons	80	80	80
BTU	960,000	900,000	900,000
CFM	12,000-18,000	10000	18000
Operating temp range	30°-110°F	64°-113°F	64°-113°F
Refr type	R-410A	R-410A	R-410A
Evap duct Size	2x20"	3x20"	4x20"
Con duct size	2x20"	3x20"	4x20"
Blower	25hp	15hp	30hp
Heat Capacity	N/A	N/A	130 kW
Power	480V 3 ph	460V 3 ph	460V 3 ph
Connections	Cam-Lock	Cam-Lock	Cam-Lock
Length	130"	216"	182"
Width	88"	82"	96"
Height	98"	100 1/4"	109"
Weight	7,500 lbs	10,250 lbs	10,300 lbs
Mounted	Skid	Skid	Skid



Rental Chiller equipment is dispatched from one of our Mobile Air & Power Rentals depots located strategically to service all of North America. All equipment is fully checked out and tested before leaving the depot to assure a trouble-free start up at the jobsite. Our equipment offers superior packaging which makes it very service-friendly for hook up and serving on the jobsite.

We understand that not every equipment outage can be foreseen, and therefore, we are on call 24/7 to meet your emergency needs. By calling our toll free number, you will quickly be put in touch with one of our rental managers who can work with you to understand your cooling needs and recommend the right solution.

We provide reliable industrial cooling solutions for all industries, including hospitals, manufacturing facilities, retail, schools, office buildings, commercial buildings, and more. We can accommodate both short and long term needs, emergency as well as planned equipment outages.

Air-Cooled Chillers	10 – 527 tons Skid Mount (up to 267 tons) & Trailer Mounted (300 tons and up) Integral Pumps built-in Single point power connection
Water-Cooled Chillers	200 – 1000 tons Containerized Single point power connection
Cooling Towers	125 – 1000 tons Open & Closed Loop Towers Skid & Trailer Mounted Stainless Steel Basins
Air-Handlers	6,000 – 27,500 cfm Low – Temp Air Handlers VFD's & Filter Racks Cold & Hot Water Coils w/ Electric Heat Strips
Rental Accessories	Hoses, Cam-lock Cable, Flex Duct, Manifolds & Specialty Fittings Pumps, Trailers, Heat Exchangers, Transformers, Switch Gear, Distro & I-Lines Panels Buffer & Volume Tanks (40 gallons – 20,000 gallons)

WATER COOLED CHILLERS

Mobile Air Portable Water Cooled Centrifugal Chiller packages are self-contained and specifically engineered to provide flexible, temporary chilled fluid for commercial and industrial air conditioning and process cooling applications. The chiller package is permanently mounted inside an ISO corrugated shipping container with a rugged steel frame and chassis that can be easily maneuvered. These on-board features allow for quick delivery and minimal installation time.



500 TON RENTAL WATER COOLED CHILLER



1000 TON RENTAL WATER COOLED CHILLER

Manufacturer	York	York
Model	YK0500	YK1000
Tons	500	1000
BTU	6,000,000	12,000,000
Evap Minimum	1,250 GPM	2,280 GPM
Evap Nominal	1,196 GPM	2,280 GPM
Evap Maximum	1,250 GPM	2,280 GPM
Evap Barrel Vol	93 gallons	200 gallons
Evap Max Side Pressure	150 PSIG	150 PSIG
Evap Fluid Conn	6" grooved	6" grooved
Cond Min	1250 GPM	2850 GPM
Cond Design	1502 GPM	2850 GPM
Cond Max	1250 GPM	2850GPM
Cond Barrel Vol	196 gallons	77 gallons
Cond Pressure Drop	7.5 psi	33°-109°F
Cond Max Side Pressure	150 PSIG	150 PSIG
Cond Fluid Conn	6" Grooved	6" Grooved
Set Point	55 - 44	55 - 44
Number of Circuits	2-pass	2-pass
Connection Type	Series 16 Camlock	Series 16 Camlock
Power	460v/3/60	460v/3/60
Connections per phase	2 Breaker	3 Breaker
Length	20' MIN CIRC	22'3" MIN CIRC
Width	537"	1085"
Height	9' 6"	9' 6"
Shipping Weight	27,143 lbs	39,059 lbs
Operating Weight	29,281 lbs	42,960 lbs
Mounted	N/A	N/A

AIR COOLED CHILLERS

Mobile Air Portable Air Cooled Scroll Chiller packages are self-contained and specifically engineered to provide flexible, temporary chilled fluid for commercial and industrial air conditioning and process cooling applications. The chiller package is permanently mounted on a rugged steel tubular frame that can be easily maneuvered with a forklift. These onboard features allow for quick delivery and minimal installation time.



5 TON RENTAL AIR COOLED CHILLER



12 TON RENTAL AIR COOLED CHILLER

Manufacturer	Americool	Americool
Model	WWC-500	WWC-1200
Tons	5	12
BTU	60,068	146,000
Flow Rate	39 GPM	72 GPM
Fluid Connections	1" Camlock	1.5" Camlock
Operating Range	41°-113°F	41°-113°F
Chilled Water Setpoints	41°-86°F	41°-86°F
Refrigerant Circuits	1	1
Refrigerant Type	410A	410A
Compressor Type	Scroll	Scroll
Power Volts ph Hz	220V 3 Ph 60 Hz	460V Ph 60 Hz
Power Connection	Camlock	Camlock
FLA	18	21
Circuit size	25 Amps	30 Amps
Length	27"	36"
Width	49"	58"
Height	52"	65"
Shipping Weight	600 lbs	900 lbs
Operating Weight	551 lbs	864 lbs
Mounted	Casters	Casters

AIR COOLED CHILLERS



**24 TON RENTAL
AIR COOLED
CHILLER**

**25-40 TON RENTAL
AIR COOLED
CHILLER**

**50-66 TON RENTAL
AIR COOLED
CHILLER**

Manufacturer	York	York	York
Model	YCAL024	YCAL033	YCAL064
Tons	22.4	35	64
BTU	288,000	420,000	768,000
Flow Rate	70 GPM	68 GPM	150 GPM
Fluid Connections	4" victaulic groove	4" victaulic groove	4" victaulic groove
Operating Range	25-70°F	10-70°F	25-115°F
Chilled Water Setpoints	50.2°F	10-70°F	25-55°F
Refrigerant Circuits	2	2	2
Compressor Type	Scroll	Scroll	Scroll
Power	208V 3 Ph 60 Hz	208V 3 Ph 60 Hz	208 3 60 & 460 3 60
FLA	58 Amps	70 Amps	137 Amps
Circuit size	51 Amps	65 Amps	128 Amps
Power Connection	Camlock	Camlock	Camlock
Length	9'	15'	10'
Width	4'	8'	8'
Height	7' 7"	8'	8' 6"
Shipping Weight	3,757 lbs	4,500 lbs	5,195 lbs
Operating Weight	3,275 lbs	5,000 lbs	6,651 lbs
Mounted	Skid	Skid	Skid

AIR COOLED CHILLERS



**80 TON RENTAL
AIR COOLED
CHILLER**

**90-120 TON RENTAL
AIR COOLED
CHILLER**

**150-180 TON RENTAL
AIR COOLED
CHILLER**

**180-220 TON RENTAL
AIR COOLED
CHILLER**

Manufacturer	York	York	York	York
Model	YCAL094	YCAL104	YLAA155	YCAV207
Tons	94	104	155	207
BTU	1,128,000	1,248,000	1,860,000	2,484,000
Flow Rate	225 GPM	239 GPM	343 GPM	474 GPM
Fluid Connections	4" victaulic groove	4" grooved	4" grooved	4" grooved
Operating Range	0°-115°F	0°-115°F	0°-125°F	0°-125°F
Chilled Water Setpoints	40°-55°F	10 - 70°F	40°-60°F	15°-60°F
Refrigerant Circuits	2	2	2	2
Compressor Type	Scroll	Scroll	Scroll	Screw
Power	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz
FLA	211 Amps	193 Amps	330 Amps	285 Amps
Circuit size	201 Amps	203 Amps	343 Amps	319 Amps
Power Connection	Camlock	Camlock	Camlock	Camlock
Length	12' 6"	14'	15' 6"	22' 9"
Width	7' 6"	7' 6"	7' 3"	7' 3"
Height	8'	8' 6"	8' 3"	8"
Shipping Weight	7,038 lbs	7,943 lbs	9,600 lbs	17,880 lbs
Operating Weight	7,888 lbs	8,867 lbs	10,500 lbs	15,900 lbs
Mounted	Skid	Skid	Skid	Skid

AIR COOLED CHILLERS



**200 TON RENTAL
AIR COOLED
CHILLER**

**225 TON RENTAL
AIR COOLED
CHILLER**

**230-260 TON RENTAL
AIR COOLED
CHILLER**

Manufacturer	Trane	Trane	York
Model	RTA200	RTAE225	247
Tons	200	225	247
BTU	240,000	270,000	2,964,000
Flow Rate	450 GPM	516 GPM	570 GPM
Fluid Connections	6" grooved	6" grooved	4" grooved
Operating Range	0°-140°F	0°-140°F	0°-125°F
Chilled Water Setpoints	40°-55°F	40°-55°F	40°-60°F
Refrigerant Circuits	2	2	2
Compressor Type	Scroll 2	Scroll 2	Screw
Power Volts ph Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz
FLA	400 Amps	450 Amps	356 Amps
Circuit size	219 amps	219 amps	397 Amps
Power Connection	Camlock	Camlock	Camlock
Length	312"	300"	22' 8"
Width	102"	93"	7' 3"
Height	105"	105"	8'6"
Shipping Weight	17,000 lbs	18,000 lbs	19,950 lbs
Mounted	Skid	Skid	Skid

AIR COOLED CHILLERS



**300 TON RENTAL
AIR COOLED
CHILLER**

**400 TON RENTAL
AIR COOLED
CHILLER**

**440 TON RENTAL
AIR COOLED
CHILLER**

**500 TON RENTAL
AIR COOLED
CHILLER**

Manufacturer	York	York	York	York
Model	YCAV307	YCAS400	YCAS440	YCAV507
Tons	307	400	440	507
BTU	3,684,000	4,800,000	5,280,000	6,084,000
Flow Rate	727 GPM	1008 GPM	1008 GPM	1179 GPM
Fluid Connections	6" grooved	6" grooved	6" grooved	6" grooved
Operating Range	0°-125°F	0°-115°F	0°-115°F	0°-125°F
Chilled Water Setpoints	25°-60°F	0°-55°F	0°-55°F	40°-60°F
Refrigerant Circuits	3	4	4	2
Compressor Type	Screw	Screw	Screw	Screw
Power Volts ph Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz	460V 3 Ph 60 Hz
FLA	538 Amps	672 Amps	812 Amps	867 Amps
Circuit size	579 Amps	800 Amps	1000 Amps	1000 Amps
Power Connection	Camlock	Camlock	Camlock	Camlock
Length	45'	48'	48'	53'
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	12' 10"	13' 6"	13' 6"	13' 6"
Shipping Weight	41,500 lbs	40,981 lbs	41,466 lbs	47,390 lbs
Mounted	Trailer	Trailer	Trailer	Trailer

COOLING TOWERS

SPOT COOLING SOLUTIONS

Mobile Air Portable Fluid Cooler Packages are specifically engineered to provide temporary fluid cooling for commercial and industrial air conditioning and process cooling applications. The fluid cooler package is permanently mounted on a rugged steel tubular frame that can be easily maneuvered with a forklift. These features allow for quick delivery and minimal installation time.



**318 TON
FLUID
COOLER**

**500 TON RENTAL
COOLING
TOWER**

**1000 RENTAL
COOLING
TOWER**

Manufacturer	Evapco	Evapco	Evapco
Model	FC0318	CT0500	CT1000
Tons	300	500	1,000
Voltage/Phase/Hz	460V/3/60Hz	460V/3/60Hz	460V/3/60Hz
Running Load Amps	N/A	70A	145A
AMP Capacity	250A	150A	180A
Overcurrent Protection	300A	N/A	N/A
Full Load Amps	200A*	34	68
Power Connections	Series 16 Cam Lock	Series 16 Cam Lock	Series 16 Cam Lock
HP	25	25	25
RPM	1750	1750	1750
Type	TEFC	TEFC	TEFC
Number of Fans	N/A	2	4
Pipe Connection / Size"	2 Basin 4" Grooved	2 Basin 10" Grooved, 2 Hard Deck 6" Grooved	3 Basin 10" Grooved, 4 Hard Deck 6" Grooved
Flow Rate	3,500 GPM	1,500 GPM	3,000 GPM
Fluid Pressure Drop	15.8 PSIG	15.8 PSI	15.8 PSI
Entering Water Temp	95°F	95°F	95°F
Leaving Water Temp	85°F	85°F	85°F
Wet Bulb Temp	78°F	78°F	78°F
Evaporated Water Rate	3.5 GPM	1.7 GPM	3.2 GPM
Maximum Water Side Pressure	150 PSIG	150 PSIG	150 PSIG
Dimensions (L X W X H)	50' X 8' X 11'	25' X 8' 10'6"	49' X 8' 10'6"
Total Shipping Weight	18,000 lbs	8,370 lbs	16,740 lbs
Total Operating Weight	32,500 lbs	15,590 lbs	31,180 lbs
Mounted	SKID	TRAILER	TRAILER
Special Package Options	Starter Panel w/100' Cable, 0F Ambient Operation *(12kW heater package + pumps)	Starter Panel w/100' Cable, 0F Ambient Operation (12kW heater package)	Starter Panel w/100' Cable, 0F Ambient Operation (12kW heater package)

HEATWAVE

Mobile Air is the leading heating and cooling expert in the country, with the sales and service benefits to customer that exceed expectations.



THE STRENGTH OF THE MOBILE AIR & POWER RENTALS TEAM INCLUDES:

- An expanded service area
- Easier access to strategically placed, fully stocked warehouses
- A broader network of sales and distribution representatives
- Increased responsiveness in urgent and emergency situations
- A greater selection of equipment and accessory options for rental and permanent placement

GETTING WARMER: HEAT FOR EVERY PURPOSE

From remote energy exploration operations to universities and manufacturing facilities, every customer site has unique heating requirements. Our team of experts evaluates each site, identifying specific needs and recommending a customized heating solution.

Some examples of industries and facilities we serve are:

- Construction
- Paint & coating
- Power plants
- Food & beverage
- Oil & gas
- Mining operations
- Refineries
- Universities & educational institutions
- Remediation projects
- Municipal sites
- Pipeline operations
- Processing & manufacturing plants

TARGETED HEAT: JUST THE RIGHT SYSTEM

Prescribing the right equipment and configuration for a specific application results in efficient, economical heating.

The Mobile Air & Power Rentals team is known for providing powerful, targeted solutions with the following equipment:

- Direct fired heaters
- Indirect fired heaters
- Portable, trailer-mounted & self-contained heaters
- Skid-mounted industrial heaters
- Electric heaters

ELECTRIC HEATERS

SAFE FOR SMALL SPACES

Situations when natural gas is unavailable and propane is out of the question, electric has you covered

IAQ ready for occupied spaces
Dry heat is a must in small spaces



**1.5KW RENTAL
ELECTRIC HEATER**

**9KW RENTAL
ELECTRIC HEATER**

**10KW RENTAL
ELECTRIC HEATER**

**15KW RENTAL
ELECTRIC HEATER**

Make	Patron	Heat Wagon	Americool	Fostoria
Model	E1.5	EL -P900	WFHE-10	EH-15-1
BTU	5,100	30,500	33,700	51,180
kW	1.5kW	9kW	10kW	15kW
Discharge CFM	116	350	806	1,070
Temp rise	32°-100°F	100°F	40°F	46°F
Width	11"	18"	15.5"	29"
Length	12"	22"	22.4"	25"
Height	8"	12"	22.2"	39"
Weight	13.7 lbs	48 lbs	59.3 lbs	65 lbs
Power	120v	240/1/60	240/1/60	240/1/60
Circuit Size	12.5 A	40 A	42.6 A	63 A
Power connection	NEMA 5-15P	50 A non-NEMA CS6365C	50 A non-NEMA CS6365C	50 A non-NEMA CS6365C
DB	47	N/A	50	N/A

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

ELECTRIC HEATERS



**15KW RENTAL
ELECTRIC HEATER**

**15KW RENTAL
ELECTRIC HEATER**

Make	Fostoria	Americool
Model	EH-15-3	WFHE-10
BTU	51,180	52,000
kW	15kW	15kW
Discharge CFM	1,070	1,103
Temp rise	46°F	40°F
Width	29"	16.6"
Length	25"	24.4"
Height	39"	23"
Weight	65 lbs	86.2 lbs
Power	240/3/60	208v/3/60
Circuit Size	42 A	36 A
Power connection	50 A non-NEMA CS6365C Plug	50 A non-NEMA CS6365C Plug
DB	N/A	N/A

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

ELECTRIC HEATERS



**20KW RENTAL
ELECTRIC HEATER**



**30KW RENTAL
ELECTRIC HEATER**

Make	Heat Wagon	AmeriCool
Model	EL-P1800-3	WFHE-30
BTU	65,000	101,350
kW	20kW	30kW
Discharge CFM	590	1,441
Temp rise	100°F	40°F
Width	14"	18.6"
Length	30"	24.4"
Height	20"	24.6"
Weight	62 lbs	113.1 lbs
Power	240/3/60 or 240/1/60	480/3/60
Circuit Size	75 A	35.92 A
Power connection	50 A non-NEMA CS6365C Plug	50 A Plug non-NEMA 7765C Plug
DB	N/A	N/A

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

ELECTRIC HEATERS



**40KW RENTAL
ELECTRIC HEATER**



**60KW RENTAL
ELECTRIC HEATER**

Make	Heat Wagon	Heat Wagon
Model	EL-P4000	EL-P6000
BTU	136,000	204,700
kW	40kW	60kW
Discharge CFM	1,800	1,800
Temp rise	100°F	100°F
Width	20"	20"
Length	46"	46"
Height	25"	25"
Weight	130 lbs	158 lbs
Power	480/3/60	480/3/60
Circuit Size	50 A	75 A
Power connection	50 A Plug non-NEMA 7765C Plug	Series 16 Camlock
DB	N/A	50A Plug

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

ELECTRIC HEATERS



60KW RENTAL ELECTRIC HEATER



150KW RENTAL ELECTRIC HEATER

Make	AmeriCool	Campo
Model	SDRA-60-93	Blaze 150E
BTU	204,720	512,000
kW	60kW	150kW
Discharge CFM	2,700	14,500
Temp rise	70°-172°F	250°F
Width	30.25"	31.5"
Length	44"	68"
Height	38.5"	56"
Weight	220 lbs	950 lbs
Power	480/3/60	480/3/60
Circuit Size		196 A
Power connection		Series 16 Camlock
DB	50A Plug	75

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

INDIRECT-FIRED AND TRAILER HEAT

UNDER EXTREME CONDITIONS



EXTREME CIRCUMSTANCES REQUIRE EXTREME PERFORMANCE

Our equipment rises to the challenge, providing rugged, efficient and incredibly reliable service in some of the world's harshest environments. The IDF SC03 and SC05 are the superstars of heating—trailer-ready, portable, and diesel-fueled for use in even the most remote locations.

APPLICATIONS:

- Bridge/roadwork repair & painting
- Refineries
- Power plants
- Tank coating & painting
- Processing facilities
- Food & beverage operations
- Construction projects that require 100% IAQ clean air
- Mining operations
- Confined spaces requiring ventilation & heated air

BENEFITS:

- Trailer-ready & portable on the job site
- Self-contained heater with built-in diesel fuel tank and generator
- 100% IAQ clean air
- No combustion bi-products in the air stream
- No exposed flame
- Heavy duty backward inclined blowers for large CFM output and static pressure
- 200°F temperature rise at 0°F incoming air
- Operational down to -40°F
- CSA approved for U.S. and Canada

INDIRECT-FIRED

INDUSTRIAL GRADE

SELF CONTAINED

EXCLUSIVE PROVIDER OF  **TIOGA**
Air Heaters
a division of Resolute Industrial



**700,000 BTU RENTAL
IDF HEATER**



**1,000,000 BTU RENTAL
IDF HEATER**

Make	Tioga Air Heaters	Tioga Air Heaters
Model	IDF-3 SCO	IDF-5 SCO
BTU	700,000	1,000,000
CFM	3,000	5,000
Discharge or Duct Ø"	16	18
ESP	3"	3"
Temp rise from 0°F	200	200
Generator Size	12.5 kW	15 kW
Firing type	Indirect	Indirect
Fuel Type	Diesel Fuel	Diesel Fuel

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

INDIRECT-FIRED

INDUSTRIAL GRADE

SUPERSTARS OF HEAT

These powerful models offer a long list of benefits:
Easier access to strategically placed, fully stocked warehouses
Increased responsiveness in emergency situations
A greater selection of equipment and accessory options for rental and permanent placement



**500,000 BTU RENTAL
IDF HEATER**



**1,400,000 BTU RENTAL
IDF HEATER**



**2,000,000 BTU RENTAL
IDF HEATER**

Make	LB White	Tioga Air Heaters	Campo
Model	Forman 500	IDF-7 DGO	Blaze 2000
BTU	500,000	1,400,000	2,000,000
CFM	3,000	7,000	16,000
Width	32"	88"	33.25"
Length	94"	176"	144"
Height	53"	88"	67"
Weight	850lbs	7,320lbs	2,950lbs
Discharge or Duct Ø"	2x12/1x16	20	1x24
Power	120v	208-240 Vac / 3 Phase / 60 Hz 480 Vac / 3 Phase / 60 Hz	208-240 Vac / 1 Phase / 60 Hz 208-240 Vac / 3 Phase / 60 Hz
FLA	13.5 amps	26A @ 240V / 3 Phase 13A @ 480V / 3 Phase	55A @ 240V / 1 Phase 32A @ 240V / 3 Phase
Fuel Type	Diesel Fuel or NG or LPG	Natural Gas / Propane/Diesel	Natural Gas / Diesel
Horsepower	8/13.5	10 HP	
Fuel Tank Size	End		N / A

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.


INDIRECT-FIRED

INDUSTRIAL GRADE

EXCLUSIVE PROVIDER OF  **TIOGA**
Air Heaters
a division of Resolute Industrial



**2,400,000 BTU RENTAL
IDF HEATER**



**2,800,000 BTU RENTAL
IDF HEATER**



**4,200,000 BTU RENTAL
IDF HEATER**

Make	Tioga Air Heaters	Tioga Air Heaters	Tioga Air Heaters
Model	IDF-11 DGO	IDF-14 DGO	IDF-21 DGO
BTU Input	2,400,000	2,800,000	4,200,000
CFM	11,000	14,000	21,000
Width	95"	95"	95"
Length	192"	192"	384"
Height	96"	96"	114"
Weight	9,400	9,400	19,310
Discharge or Duct Ø"	24	28	32
ESP	3"	3"	3"
Temp Rise from 0°F	200	200	200
Power	208-240 Vac / 3 Phase / 60 Hz 480 Vac / 3 Phase / 60 Hz	208-240 Vac / 3 Phase / 60 Hz 480 Vac / 3 Phase / 60 Hz	208-240 Vac / 3 Phase / 60 Hz 480 Vac / 3 Phase / 60 Hz
FLA	44A @ 240V / 3 Phase 22A @ 480V / 3 Phase	45A @ 240V / 3 Phase 23A @ 480V / 3 Phase	55A @ 240V / 3 Phase 28A @ 480V / 3 Phase
Firing type	Indirect Natural Gas / Propane/Diesel	Indirect Natural Gas / Propane/Diesel	Indirect Natural Gas / Propane/Diesel
Horsepower	15 HP	15 HP	20 HP
Fuel Tank Size	280 Single Wall 270 Double Wall	280 Double Wall	N/A

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

DIRECT-FIRED

PORTABLE UNITS



**80,000 BTU RENTAL
DF HEATER**



**170,000 BTU RENTAL
DF HEATER**



**350,000 BTU RENTAL
DF HEATER**



**400,000 BTU RENTAL
DF HEATER**

Make	LB White	LB White	LB White	Tioga Air Heaters
Model	LB 80	LB 170	LB 350	AH-4
BTU	80,000	170,000	350,000	400,000
CFM	450	1,200	2,600	1,800
Width	13.5"	18.25"	22.25"	28"
Length	29.5"	30.75"	48"	57"
Height	20"	28.25"	32.75"	38"
Weight	79	161	320	350
Discharge Ø"	N/A	N/A	N/A	12
Power	120	120	120	120
FLA	5.0A	7.5A	10A	15A
Circuit Size	15	15	15	20A
Temp Rise	170°F	170°F	170°F	190°F
Firing Type	On-Off	On-Off	On-Off	Hi-Lo Fire
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS			


Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

DIRECT-FIRED

PORTABLE UNITS



500,000 BTU RENTAL DF HEATER 750,000 BTU RENTAL DF HEATER 990,000 BTU RENTAL DF HEATER 990,000 BTU RENTAL DF HEATER

Make	Tioga Air Heaters	Tioga Air Heaters	Tioga Air Heaters	Tioga Air Heaters
Model	AH-5	AH-7	AH-9	AH-10
BTU	500,000	750,000	990,000	990,000
CFM	3,000	4,000	5,000	6,000
Width	31"	34"	34"	34"
Length	74"	85"	85"	81"
Height	45"	47"	47"	51"
Weight	590	700	720	720
Discharge Ø"	16	16	18	18
Power	120	208-240 / 480Vac	208 - 240 Vac / 1 Phase	208 - 240 Vac / 1 Phase
FLA	17A	18A @240V 1 ph 10A @ 240V 3ph 5A @ 480V 3 ph	18A @ 240 Vac / 1 Phase 10A @ 240 Vac / 3	18A @ 240 Vac / 1 Phase 10A @ 240 Vac / 3
Circuit Size	25A			
Temp Rise	190°F	190°F	190°F	190°F
Firing Type	Full Modulating	Hi Low Fire	Hi Low Fire	Full Modulating
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS			




CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DIRECT-FIRED

PORTABLE UNITS



1,500,000 BTU RENTAL 2,000,000 BTU RENTAL 2,400,000 BTU RENTAL 2,500,000 BTU RENTAL

Make	Tioga Air Heaters	Tioga Air Heaters	Tioga Air Heaters	Campo
Model	SSF-1502 (A15)	AH-22	DF-11	DF-2500
BTU	1,500,000	2,000,000	2,400,000	2,500,000
CFM	7,000	12,000	11,000	14,737
Width Inches	45"	60"	72"	31.50"
Length Inches	100"	101"	168"	111"
Height Inches	59"	64"	77"	78.45"
Weight LBS	1,440	2,200	2,400	1,640
Discharge Ø"	24	24	24 or 25 x 34 Rect	
Power	208 - 240 Vac / 1 Phase 480 Vac/3 Phase	208 - 240 Vac / 1 Phase 480 Vac / 3 Phase	208 - 240 Vac / 3 Phase 460 Vac / 3 Phase	230 Vac / 1 Phase 230 Vac / 3 Phase
FLA	24A @ 240 Vac / 1 Phase 15A @ 240 Vac / 3	40A @ 240 Vac / 1 Phase 22A @ 240 Vac / 3	22A @ 240 Vac / 3 Phase 11A @ 480 Vac / 3 Phase	
Temp Rise	200°F	190°F	200°F	200°F
Firing Type	Modulating-Hi-Lo	Full Modulating	Lo-Hi-Lo	Modulating
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS			



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DIRECT-FIRED

PORTABLE UNITS



2,500,000 BTU RENTAL **4,200,000 BTU RENTAL** **4,500,000 BTU RENTAL** **4,500,000 BTU RENTAL**

Make	Tioga Air Heaters	Tioga Air Heaters	Tioga Air Heaters	Campo
Model	SSF-4002 (A25)	DF-21	DF-25	DF-4500
BTU	2,500,000	4,200,000	4,500,000	4,500,000
CFM	15,000	21,000	25,000	24,390
Width Inches	53"	90"	91"	43.50"
Length Inches	136"	186"	192"	125"
Height Inches	69"	95"	88"	78.50"
Weight LBS	2,650	5,200	5,500	2,326
Discharge Ø"	30	32 or 29 x 41 Rect	32 or 29 x 41 Rect	
Power	208 - 240 / 480 Vac 3 Phase	208-240 / 460 Vac 3 Phase	208-240 / 460 Vac 3 Phase	208-240 / 460 Vac 3 Phase
FLA	34A @ 240 Vac / 3 Phase 17A @ 480 Vac / 3 Phase	42A @ 240 Vac / 3 Phase 21A @ 480 Vac / 3 Phase	50A @ 240 Vac / 3 Phase 25A @ 480 Vac / 3 Phase	
Temp Rise	200°F	190°F	190°F	200°F
Firing Type	Modulating-Hi-Lo	Modulating-Hi-Lo	Full Modulating	Modulating
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas /Propane Vapor	Natural Gas / Propane
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS			



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DIRECT FIRED (TUBE)

HEATERS

BIG HEAT OUTPUT

Designed properly and implemented correctly, moisture control, building safety, even heat and fuel savings can be addressed without blowing up the budget.



155,000 BTU RENTAL TUBE HEATER **170,000 BTU RENTAL** **250,000 BTU RENTAL TUBE HEATER** **400,000 BTU RENTAL**

Make	LB White	Heat Star	Rexotherm	LB White
Model	CP 155	HS170	ROT-250	CP 400
BTU	155,000	170,000	250,000	400,000
Air Flow CFM	625	450	1,650	1,582
Width	9 1/12"	26.5"	22.5"	12.5"
Length	24"	11.5"	36"	34.5"
Height	16"	16.5"	26"	21.5"
Weight	100	31.16	105	51
Power	120	115v/3 amp	114	120
Amps FLA 120V	4	7.5A	10	4
Circuit Size	15	15	15	15
Temp Rise		170°F		
Firing Type	On-Off	On-Off	On-Off	On-Off
Fuel Type	Natural Gas / Propane Vapor	Propane Vapor	Natural Gas / Propane Vapor	Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS			



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DIRECT FIRED (TUBE) HEATERS



**400,000 BTU RENTAL
TUBE HEATER**



**400,000 BTU RENTAL
TUBE HEATER**



**500,000 BTU RENTAL
TUBE HEATER**

Make	Sure Flame	Rexotherm	Tioga Air Heaters
Model	S405	ROT-400	Z500
BTU	400,000	400,000	500,000
Air Flow CFM	2,000	1,250	2,800
Width	18"	25"	26"
Length	46"	43"	52"
Height	24"	33"	33"
Weight	95	215	250
Voltage	120	115	120
Amps FLA 120V	12	10	10
Circuit Size	15	15	15
Temp Rise	340°F		
Firing Type	On-Off	On-Off	On-Off
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS		

DIRECT FIRED (TUBE) HEATERS



**750,000 BTU RENTAL
TUBE HEATER**



**800,000 BTU RENTAL
TUBE HEATER**



**950,000 BTU RENTAL
TUBE HEATER**

Make	Heat Wagon	Rexotherm	Heat Wagon
Model	1800	ROT-800	950
BTU	750,000	800,000	950,000
Air Flow CFM	4,200	1,800	7,000
Width	26"	28"	31"
Length	48.5"	49"	73"
Height	31.5"	37"	39"
Weight	200	260	325
Voltage	120	115	115
Amps FLA 120V	15	15	15
Circuit Size	15	15	15
Temp Rise	385°F		250°F
Firing Type	Hi-Lo-Off	On-Off	Hi-Lo-Off
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS		

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

DIRECT FIRED (TUBE) HEATERS



**1,000,000 BTU RENTAL
TUBE HEATER**



1,250,000 BTU RENTAL TUBE HEATER

Make	Heat Wagon	Rexotherm
Model	2000	ROT-1500
BTU	1,000,000	1,250,000
Air Flow CFM	4,200	3,800
Width	26"	29.25"
Length	62"	49"
Height	30"	40.5"
Weight	230	300
Power	115	115
Amps FLA	12	15
Circuit Size	15	
Temp Rise	490°F	
Firing Type	Hi-Lo-Off	
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS	

DIRECT FIRED (TUBE) HEATERS



**1,500,000 BTU RENTAL
TUBE HEATER**



**1,500,000 BTU RENTAL
TUBE HEATER**



**2,000,000 BTU RENTAL
TUBE HEATER**

Make	Sure Flame	Frost Fighter	Heat Wagon
Model	S1505	DF 1500	2730
BTU	1,500,000	1,500,000	2,000,000
Air Flow CFM	7,000	7,000	12,500
Width	32"	40"	32"
Length	69"	75"	72"
Height	42"	53"	46"
Weight	300	415	440
Power	115	115	208-230 / 460 V
Amps FLA	15	20	30 / 20 / 15
Circuit Size	15	15	15
Temp Rise	490°F	200°F	250°F
Firing Type	Hi-Lo-Off	Hi-Lo-Off	Hi-Lo-Off
Fuel Type	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor	Natural Gas / Propane Vapor
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS		



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DIRECT FIRED (TUBE) HEATERS



**2,000,000 BTU RENTAL
TUBE HEATER**

**3,250,000 BTU RENTAL
TUBE HEATER**

**3,500,000 BTU RENTAL
TUBE HEATER**

Make	Rexotherm	Rexotherm	Heat Wagon
Model	ROT-2500	ROT-3000	3050
BTU	2,000,000	3,250,000	3,500,000
Air Flow CFM	6,600	18,500	16,000
Width	41"	39"	41"
Length	61"	77"	73"
Height	52"	58"	44"
Weight	475	500	570
Power	208-230 / 460 V	460 V	208-230 / 460 V 3 Phase
Amps FLA	22 Amps @ 208-230 V, 1 Phase 15 Amps @ 208-230 V, 3 Phase	5 Amps @ 460 Volt, 3 Phase	24 Amps @ 208-230 Volt, 1 Phase 12 Amps @ 208-230 Volt, 3 Phase
Circuit Size	30/20/15	10	30/20/15
Temp Rise			200°F
Firing Type			Hi-Lo-Off
Fuel Type	Natural Gas / Propane	Natural Gas / Propane	Natural Gas / Propane
Gas pressure	Contact your Mobile Air representative for pressure under 1 PIS		



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

GROUND THAW HEATERS

BIG HEAT OUTPUT

Designed properly and implemented correctly, moisture control, building safety, even heat and fuel savings can be addressed without blowing up the budget.



**259,000 BTU RENTAL
GROUND THAW HEATER**

**259,000 BTU RENTAL
GROUND THAW HEATER**

**320,700 BTU RENTAL
GROUND THAW HEATER**

Make	Frost Buster	Tioga	Wacker Neuson
Model	LD5030	Hydro Heat 300	E3000
BTU	259,000	259,000	320,700
Width	96"	96"	98"
Length	208"	192"	189"
Height	102"	102"	95"
Weight	4800 lbs	9690 lbs	8200 lbs



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

Could your project benefit from a higher level of documented construction heat safety plan? If so, Mobile Air & Power Rentals has a comprehensive documented process for even the highest level of construction users in the industry. A written safety and maintenance plan to help and certify that everything is complete, from soup to nuts.

CREATE A SAFE ENVIRONMENT

DOCUMENTED SAFETY HEAT PROGRAM FOR YOUR CONSTRUCTION PROJECT:

PROVIDE PORTABLE COMMERCIAL AND INDUSTRIAL CONSTRUCTION READY EQUIPMENT that meets or exceeds the ANSI Standard Z83.7.

QUALIFIED PERSONNEL that have the knowledge, experience, and technical skills of the heating products.

PREVENTATIVE MAINTENANCE PROGRAM that encompasses the entire construction heater operation, safety and tested run performance in the shop.

DOCUMENTED ON-SITE SAFE START-UP OF EACH CONSTRUCTION HEATER TO CONFIRM:

- Fuel leak check
- Proper burner adjustment
- Gas pressure regulation confirmation
- Electrical confirmation
- Proper heater placement
- Safety lock-out checks

- TOOL BOX SAFETY TALK**
- Proper start-up and shut-down of the heater
 - Safety features of each heater
 - Emergency shut off locations and use
 - Location and identification of gas lines
 - What to do if there is a gas leak
 - Discuss the properties and safety concerns for natural gas or propane
 - Review proper heater placement
 - What to look for on a daily basis when walking by the heater

- DOCUMENTED SERVICE REPORTS**
- Planned and unplanned maintenance or repair records
 - Heater relocation and new start-up



OAKLAND UNIVERSITY HUMAN HEALTH BUILDING

DATA...IT'S ALL ABOUT RISK MITIGATION AND EARLY WARNING!

The Mobile Air & Power Rentals Remote Monitoring System (RT-RM) performs humidity and temperature snapshots every 15 minutes. These readings are saved in the cloud. And, a comprehensive history of the indoor environment of your building is built to provide both a graphical chart and spreadsheet.

KEEP YOUR JOB ON TRACK. Verifying with written documentation the environmental conditions to help prove to your sub-contractors that work can be performed as scheduled with verification of temperature and humidity that are within range to continue your schedule.


WARRANTY VERIFICATION. Hard copy in hand of the past temperature and humidity conditions to help establish the correct product storage, application installation of materials, etc., to mitigate your exposure to future claims, if any.

EARLY WARNING. Immediate verification of temperature or humidity conditions outside a set parameter. Text, email or direct calls go straight to both your job site and Mobile Air to help correct problems before they cause potential delays in the building schedule.



SIMPLE TO USE

Easy to set up for use on your site. Priceless information in your back pocket.



HUMIDITY AND TEMPERATURE READING VERIFIED
 SAMPLES FROM OAKLAND UNIVERSITY CONSTRUCTION PROJECT

JOB TRACKING

MOBILE Air & Power Rentals

Date: 02/26/2012
 Company: THE CHRISTMAN COMPANY
 Job: OAKLAND UNIVERSITY HUMAN HEALTH BUILDING
 City: LANSING State: MI

DeviceName	DeviceID	DeviceType	Location	ReadingDate/Time	ReadingTemp	ReadingHumidity
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 10:31:00 PM	61.6	Temperature
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 10:08:00 PM	51	Humidity
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 10:00:00 PM	63.6	Temperature
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 9:30:00 PM	52	Humidity
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 9:30:00 PM	63.6	Temperature
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 8:30:00 PM	51	Humidity
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 8:30:00 PM	64.5	Temperature
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 8:00:00 PM	64.5	Humidity
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 8:00:00 PM	64.5	Temperature
RO4587 Macomb Mech - Oakland Univ - 3rd Floor West	104587	Macomb Mech	Oakland Univ - 3rd Floor West	4/12/2012 7:30:00 PM	51	Humidity

AIR SCRUBBERS

Mobile Airs Portable HEPA ready Air Filtration Systems provides high volume air exchanges required in abatement, dust control, and air scrubbing on large job sites contaminated by airborne pollutants. These lightweight and portable Negative Air Machines and Air Scrubbers produce up to 2000 CFM of filtered air movement to efficiently improve indoor air quality in: healthcare facilities, schools, hospitality venues, construction sites, and light industrial applications.



**1300 CFM RENTAL
AIR MOVER**



**900 CFM RENTAL
NEGATIVE AIR SCRUBBER**



**1800 CFM RENTAL
NEGATIVE AIR MACHINE**

Make	Abatement Technologies	Predator	Aerospace
Model	Raptor	Predator 200	Aeroclean 1800
CFM	1,300	300-900	1200/1800
HEPA filter size	0	0	24"x16"x11 7/8"
Power	120 VAC	120 VAC	120 VAC
Amps FLA	2.8 A	5 A	9.4 A
Circuit Size	5 A	15 A	15 A
Duct Ø"	N/A	N/A	12"
Length	20"	22"	33"
Width	17"	24"	18"
Height	18.5"	42"	26"
Weight	25 lbs	70 lbs	90 lbs
DB	N/A	67	N/A

AIR SCRUBBERS



**2000 CFM RENTAL
NEGATIVE AIR MACHINE**



**500 CFM RENTAL
AIR SCRUBBER**



**500 CFM RENTAL
AIR SCRUBBER**

Make	Xpower	Dri-Eaz	B-Air
Model	AP-2000	DefendAir 500	RA-650
CFM	2,000	250/500	up to 500
HEPA filter size	24"x24"x11.5"	0	19"x15 7/8"x 2"
Power	120 VAC	120 VAC	120 VAC
Amps FLA	8 A	3 A	2.5 A
Circuit Size	10 A	5 A	5 A
Duct Ø"	12"	12"/8"	N/A
Length	41"	27"	22"
Width	29"	19"	13"
Height	33"	25"	20"
Weight	113 lbs	44 lbs	36 lbs
DB	N/A	N/A	74



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DESICCANT DEHUMIDIFIERS

Mobile Airs fleet of dehumidifiers reduce humidity in enclosed structural environments by removing water vapor from the air through the refrigeration or desiccant process. Dehumidifiers can help dry wet materials like carpet and pad, paint and finishes, dry wall and gypcrete and other wet construction and remediation processes.



**385 CFM RENTAL
DESICCANT DEHUMIDIFIER**

**700 CFM RENTAL
DESICCANT DEHUMIDIFIER**

**1000 CFM RENTAL
DESICCANT DEHUMIDIFIER**

Make	Phoenix	STULZ	Arid-Dry
Model	D385	DRY 700	MS 1000
CFM	385	N/A	1,000
Length	21 3/8"	65.5"	29"
Width	24 1/4"	28"	81"
Height	40"	37.5"	40"
Weight	105 lbs	330 lbs	525 lbs
Water Removal GPD	19	44	58
Operating Range °F	-10°-140°F	N/A	33°-110°F
Refrig \ weight	Low Grain Refrigerant	N/A	N/A
Duct Size	12" 10"	N/A	12"/12"
Filter Size	N/A	N/A	N/A
Power	110-120v	230v	230 vac 1 ph
Amps FLA	10A	50.8	80 A
Circuit Size	20 A	20A	100 A
DB	N/A	N/A	N/A
Gas Supply	N/A	N/A	N/A
Pipe Size	N/A	N/A	N/A
BTU	N/A	N/A	191,000
Reactivation	N/A	N/A	Electric

DESICCANT DEHUMIDIFIERS



**2400 CFM RENTAL
DESICCANT DEHUMIDIFIER**

**4800 CFM RENTAL
DESICCANT DEHUMIDIFIER**

**4800 CFM RENTAL
DESICCANT DEHUMIDIFIER**

Make	Arid-Dry	Arid-Dry	Phoenix
Model	MS 2400	MS 4800	4800 P
CFM	2,400	4,800	4800
Length	89"	110"	120"
Width	29"	46"	48"
Height	58"	85"	66"
Weight	1,150 lbs	2,298 lbs	1550 lbs
Water Removal GPD	170	295	18
Operating Range °F	33°-110°F	33°-110°F	-10°-140°F
Refrig \ weight	N/A	N/A	N/A
Duct Size	12"/20"	20"	18" lay flat duct
Filter Size	12"x16"x2"	N/A	20"x20"x2
Power	230 vac 1 ph	230 vac 1 ph	240v
Amps FLA	20 A	55.2 A	50A
Circuit Size	30 A	110 A	20A
DB	N/A	N/A	N/A
Gas Supply	7"-14" NG/LP	7"-14" NG/LP	N/A
Pipe Size	1/2"	3/4"	N/A
BTU	120,000	359,000	N/A
Reactivation	Gas	Gas	N/A



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DESICCANT

DEHUMIDIFIERS



**5000 CFM RENTAL
DESICCANT DEHUMIDIFIER**

Make	ARID-Dry
Model	CDH-R-138
CFM	5000
Length	100.25"
Width	50"
Height	96"
Weight	3300 lbs
Water Removal GPD	75
Operating Range °F	33°-110°F
Refrig \ weight	N/A
Duct Size	18" or 20" round connections
Filter Size	18"x20"x2"
Power	460v
Amps FLA	21a
Circuit Size	20A
DB	N/A
Gas Supply	N/A
Pipe Size	3/4"
BTU	N/A
Reactivation	Gas or Electric



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

DESICCANT

DEHUMIDIFIERS



**5000 CFM RENTAL
DESICCANT DEHUMIDIFIER**

Make	STULZ	Arid-Dry
Model	SD2-5500-107-E	MS 15000
CFM	5000	15000
Length	N/A	221"
Width	N/A	88"
Height	N/A	101"
Weight	N/A	10,650 lbs
Water Removal GPD	N/A	190
Operating Range °F	N/A	33°-110°F
Refrig \ weight	R-140a	N/A
Duct Size	N/A	N/A
Filter Size	N/A	N/A
Power	N/A	460 vac 3 ph
Amps FLA	N/A	335 A
Circuit Size	20A	450 A
DB	N/A	N/A
Gas Supply	N/A	N/A
Pipe Size	N/A	N/A
BTU	N/A	791,000
Reactivation	N/A	Electric



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

LGR

DEHUMIDIFIERS



**150 CFM RENTAL
LGR DEHUMIDIFIER**



**230 CFM RENTAL
LGR DEHUMIDIFIER**

Make	Phoenix	Phoenix
Model	PH-R150	PH-R175
CFM	150	230
Length	20"	20"
Width	17"	20"
Height	30"	34"
Weight	82 lbs	105 lbs
Water Removal GPD	9	11
Operating Range °F	33°-110°F	33°-110°F
Refrig \ weight	R-410A / 24 oz	R-410A / 19 oz
Duct Size	10"	10"
Filter Size	12"x12"x1"	12"x12"x1"
Power	120 VAC	120 VAC
Amps FLA	5.5 A	6.3 A
Circuit Size	10 A	12 A
DB	N/A	N/A
Gas Supply	N/A	N/A
Pipe Size	N/A	N/A
BTU	N/A	N/A
Reactivation	n/a	n/a



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

LGR

DEHUMIDIFIERS



**325 CFM RENTAL
LGR DEHUMIDIFIER**



**400 CFM RENTAL
LGR DEHUMIDIFIER**



**552 CFM RENTAL
LGR DEHUMIDIFIER**

Make	Phoenix	AmeriCool	Dri-Eaz
Model	R200	ADH-130	DE-7000XLi
CFM	325	400	552
Length	20"	20"	20"
Width	20"	20"	20"
Height	33.5"	34"	34"
Weight	105 lbs	107 lbs	107 lbs
Water Removal GPD	30	16	21
Operating Range °F	33°-110°F	33°-100°F	33°-100°F
Refrig \ weight	R-410A / 10oz	R-410A / 26.8 oz	Low Grain Refrigerant
Duct Size	12/20"	N/A	N/A
Filter Size	12"x12"x1"	Washable	Washable
Power	120 VAC	120 VAC	120 VAC
Amps FLA	8.3 A	9.1 A	8.3 A
Circuit Size	20 A	15 A	12 A
DB	N/A	N/A	65 DB
Gas Supply	N/A	N/A	N/A
Pipe Size	N/A	N/A	N/A
BTU	N/A	N/A	N/A
Reactivation	N/A	n/a	n/a



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended.
All specifications subject to change without notice.

Mobile Air's fleet of dehumidifiers reduce humidity in enclosed structural environments by removing water vapor from the air through the refrigeration or desiccant process. Dehumidifiers can help dry wet materials like carpet and pad, paint and finishes, dry wall and gypcrete and other wet construction and remediation processes.



RAPTOR

VERSA-KOOL AIR

Manufacturer	Abatement Technologies Raptor	Schaefer
Air Flow	3,275	N/A
Fan Diameter	N/A	36 in
CFM	1,300	12,709
Power Supply	120V AC, 60 Hz, 15amp	N/A
HP	N/A	3/4
Volts	N/A	115
Amps	2.8	6/3.5
Circuit Breaker	10 amps	N/A
Dimensions (w x l x h)	N/A	37.5 x 37.5 x 16.5 in
Weight	25 lbs	70 lbs

STAY POWERED IN EVERY SITUATION



Mobile Air & Power Rentals is excited to now offer power solutions to our lineup of services. We understand mobile power for both short and long-term needs, allowing us to deliver what you need, when you need it.

Our rental generator range from 20-2000kW and can be used in any application, including construction sites, events, schools, hospitals, offices, retail spaces, gas and pipeline projects, and more. With our rental power

distribution solutions portable power is made easy. We offer a full line of NEMA 3R outdoor rated panels, transformers, and transfer switches. Our rental power accessories include cable, double-walled fuel tanks and more, meaning you don't have to worry about a thing.

All of our rental equipment is tested regularly, feature innovative technology and complies with worldwide standard for safe use.



CERTIFICATION OR STANDARDS DEPENDING ON UNIT.

Dedicated electric service strongly recommended. All specifications subject to change without notice.

GENERATORS

PORTABLE POWER

WE'VE GOT YOU COVERED

Our rental generator fleet consists of professionally maintained leading edge equipment. These units are designed for the rental market and have a variety of features that make these units very user-friendly. Mobile Air & Power Rentals also carries a full line of power distribution to get power where you need it, when you need it.



25KVA - 20KW RENTAL GENERATOR



25KVA - 20KW RENTAL GENERATOR



45KVA - 36KW RENTAL GENERATOR

Manufacturer	TecnoGen	MultiQuip	MultiQuip
Model	PK22TSX	WhisperWatt 25	WhisperWatt 45
Fuel Capacity	37 gallons	68 gallons	84 gallons
Run Time	24 hrs	24 hrs	24 hrs
Nominal Size rating	17 kW prime	20 kW prime	36 kW prime
Main Breaker	61 Amp	60 Amp	125 Amp
Frequency Hz	N/A	N/A	N/A
Voltage	480/208/120V	480/208/120V	480/208/120V
Connections	N/A	1/0 lug	2/10 lug
Engine Manufacturer	perkins	Isuzu	Isuzu
Length	70"	72"	74"
Width	30"	29"	35"
Height	60"	39"	49"
Weight	1,764 lbs	1,541 lbs	2,462 lbs

GENERATORS

PORTABLE POWER



50 KVA - 40 KW RENTAL GENERATOR



65KVA - 50KW RENTAL GENERATOR



70KVA - 56KW RENTAL GENERATOR

Manufacturer	Techno Gen	MMD PowerPro	MultiQuip
Model	KL50TSX	PowerPro65	WhisperWatt70
Fuel Capacity	71 gallons	106 gallons	103 gallons
Run Time	35 hrs	29 hrs	24 hrs
Nominal Size rating	39 kW prime	50 kW prime	52 kW prime
Main Breaker	N/A	167 Amp	175 Amp
Frequency Hz	60 Hz	N/A	N/A
Voltage	480/277/208/120V	480/208/120V	480/208/120V
Connections	Camlok	Lug	Lug
Engine Manufacturer	Kohler	Isuzu	Isuzu
Length	91"	144"	105"
Width	46"	70"	37"
Height	67"	73"	68"
Weight	3,025 lbs	5,500 lbs	5,920 lbs

GENERATORS

PORTABLE POWER



**85KVA - 65KW
RENTAL**

**120KVA - 95KW
RENTAL**

**125KVA - 100KW
RENTAL GENERATOR**

**150KVA - 120KW
RENTAL**

Manufacturer	MultiQuip	TecnoGen	MultiQuip	MMD PowerPro
Model	WhisperWatt85	PK113FQ-G100	WhisperWatt125	Powerpro 150
Fuel Capacity	126 gallons	158 gallons	168 gallons	215 gallons
Run Time	24 hrs	24 hrs	24 hrs	25 hrs
Nominal Size rating	65 kW prime	96 kW prime	100 kW prime	120 kW
Main Breaker	225 Amp	314 Amp	300 Amp	394 Amp
Frequency Hz	N/A	N/A	N/A	N/A
Voltage	480/208/120V	480/208/120V	480/208/120V	480/208/120V
Connections	Lug	Camlok	Lug	Lug
Engine Manufacturer	John Deere	Perkins	Isuzu	Isuzu
Length	177"	104"	120"	196"
Width	79"	43"	48"	79"
Height	70"	71"	72"	85"
Weight	7,500 lbs	5,622 lbs	8,700 lbs	9,900 lbs

GENERATORS

PORTABLE POWER



**150KVA - 120KW RENTAL
GENERATOR**

**220KVA - 176KW RENTAL
GENERATOR**

**225 KVA - 180 KW
RENTAL GENERATOR**

**630 KVA - 500 KW RENTAL
GENERATOR**

Manufacturer	MultiQuip	MultiQuip	Techno Gen	Techno Gen
Model	WhisperWatt150	WhisperWatt220	FP250TSX	VO630TSX
Fuel Capacity	214 gallons	350 gallons	283 gallons	465 gallons
Run Time	24 hrs	27 hrs	28 hrs	19 hrs
Nominal Size rating	120 kW prime	180 kW prime	201 kW prime	503 kW prime
Main Breaker	400 Amp	529 Amp	N/A	N/A
Frequency Hz	N/A	N/A	61 Hz	60 Hz
Voltage	480/208/120V	480/208/120V	480/277/208/120V	480/277/208/120V
Connections	4/0 lug	4/0 lug	camlok	Camlok
Engine Manufacturer	John Deere	Volvo	FPT	Volvo
Length	128"	144"	165"	189"
Width	48"	52"	76"	76"
Height	25"	69"	88"	94"
Weight	11,541 lbs	13,500 lbs	9,479 lbs	17,152 lbs

GENERATORS

PORTABLE POWER



1000KVA - 800KW RENTAL GENERATOR **1250KVA - 1000KW RENTAL GENERATOR** **1875KVA - 1500KW RENTAL GENERATOR** **2500KVA - 2000KW RENTAL GENERATOR**

Manufacturer	Caterpillar	Caterpillar	Caterpillar	Caterpillar
Model	XQ 800	XQ 1000	XQ 1500	XQ 2000
Fuel Capacity	1250 gallons	1,250 gallons	1,250 gallons	1,250 gallons
Run Time	23 hrs	23 hrs	12 hrs	12 hrs
Nominal Size rating	725 kW prime	920 kW prime	1360 kW prime	1825 kW prime
Main Breaker	Engine: c27 tier 4 interim, Diesel Fuel	Engine: c32 tier II ATA-AC, Diesel Fuel	Engine: c35 128, Diesel Fuel	Engine:DM8264, Diesel Fuel
Frequency Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Voltage	208-480V	208-480V	208-480V	208-480V
Connections	N/A	N/A	N/A	N/A
Engine Manufacturer	N/A	N/A	N/A	N/A
Length	360"	360"	480"	480"
Width	96"	96"	96"	96"
Height	162"	114"	162"	168"
Weight	56,207 lbs	47,000 lbs	59,000 lbs	93,000 lbs

TRANSFORMERS

NEMA 3R

PERFECT FOR ANY APPLICATION

Mobile Air & Power Rentals offer a full line of NEMA 3R weatherproof rental transformers. All transformers are custom-built for easy transport and setup at your job site. Transformer configurations include simple step up or step down.



45 KVA 120/208V ISO RENTAL TRANSFORMER

150 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER

	45 KVA 120/208V ISO RENTAL TRANSFORMER	150 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER
High Side Capacity	120/208V, 3 phase, Wye, 100 amps	480V, 3 phase, Delta, 188 amps
Low Side Capacity	120/208v, 3 phase Wye, 100 amps	120/208V, 3 phase, 433 amps
3R Rated	available	available
Load Side Disconnect	available	available
Line Side Disconnect	available	available
Connectors	Barrell Lug	Camlock
Length	30"	24"
Width	30"	36"
Height	36"	24"
Weight	700 lbs	1015 lbs
Wheels	Yes	Yes

TRANSFORMERS

NEMA 3R



150 KVA STEP DOWN RENTAL TRANSFORMER | HIPOWER SKID TYPE



300 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER



500 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER

	150 KVA STEP DOWN RENTAL TRANSFORMER HIPOWER SKID TYPE	300 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER	500 KVA 208 WYE TO 480V DELTA RENTAL TRANSFORMER
High Side Capacity	600V, 3 phase, 175 amps	480V, 3 phase, Delta, 800 amps	480V, 3 phase, Delta, 600 amps
Low Side Capacity	480V, 3 phase, 175 amps	120/208V, 3 phase, Wye, 400 amps	120/208V, 3 phase, Wye, 600 amps
3R Rated	available	available	available
Load Side Disconnect	available	available	available
Line Side Disconnect	available	available	available
Connectors	Camlock	Camlock	Camlock
Length	41.375"	36"	48"
Width	62"	36"	60"
Height	52.25"	60"	60"
Weight	1518 lbs	1,400 lbs	2,200 lbs
Wheels	Yes	Yes	Yes

POWER DISTRIBUTION

NEMA 3R

WE'LL LEAD THE WAY

Mobile Air & Power Rentals offer a full line of NEMA 3R, outdoor rated electrical distribution panels and equipment ranging in sizes. All of our equipment is perfect for places like construction sites, temporary amusement parks, entertainment venues, trade shows, convention halls, and many other temporary structures.



50 AMP RENTAL SPIDER BOX



50 AMP RENTAL DISTRIBUTION BOX



100 AMP RENTAL DISTRIBUTION BOX

	50 AMP RENTAL SPIDER BOX	50 AMP RENTAL DISTRIBUTION BOX	100 AMP RENTAL DISTRIBUTION BOX
Manufacturer	CEP Electric	Lex Products	Lex Products
Model	Spider Box 50 AMP	PowerHOUSE	PowerHOUSE
AMPS	50	50	100
Rating	50 amp, single phase (CS6375)	(1) 50 amp single phase, 3 pole, 4 wire, 120/240vacf, california-style locking inlet	100 amp, 3 phase, (H,H,H,N,G) 4 pole, 5 wire, 120/208Y VAC
Environmental Rating	NEMA V3R Water Resistant	NEMA V3R Water Resistant	NEMA V3R Water Resistant
Connector to Building Wiring	N/A	N/A	N/A
Input Connector	50 amp, 125V/250V (CS6375)	(1) 50 amp, single phase, 3 pole, 4 wire, 120/240 VAC, California-style locking inlet	(1) set of (5) 16 series Cam-type color-coded panel mount inlets
Output	50 amp, 125V/250V (CS6369)	(6) NEMA, 5-20, 20 amp, single phase, 2 pole, 3 wire, 120 VAC, GFCI duplex receptacles	(5) NEMA L21-20, 20 amp, 3 phase, 4 pole, 5 wire, 120/208Y VAC locking receptacles
Agency Approval	N/A	N/A	N/A
Material	N/A	N/A	N/A
Feed Thru	N/A	N/A	N/A
Overcurrent protection	N/A	(6) 20 amp single pole branch-rates circuit breakers	(5) 20 amp, 3 pole branch-rates circuit breakers
Width	21"	8.5"	11.5"
Length	14.5"	8.5"	11.5"
Height	11"	11"	14"
Weight	29 lbs	16 lbs	32 lbs

POWER DISTRIBUTION

NEMA 3R



100 AMP RENTAL WEATHER PROOF DISTRIBUTION BOX

200 AMP RENTAL DISTRIBUTION BOX

400 AMP RENTAL SPIDER BOX

Manufacturer	Lex Products	Lex Products	Lex Products
Model	PowerHOUSE	PowerHOUSE	Spider Box
AMPS	100	200	400
Rating	100 amp, 3 phase, (H,H,H,N,G) 4 pole, 5 wire, 120/208Y VAC	200 amp, 3 phase, (H,H,H,N,G)V4 Pole, 5 wire, 120/208VAC	400 amp, 3 phase, (H,H,H,N,G) 4 pole, 5 wire, 120/208Y VAC
Enviromental Rating	NEMA 3R Weather Resis-	NEMA V3R Water Resistant	NEMA 1 indoor
Connector to Building Wiring	N/A	N/A	N/A
Input Connector	(1) set of (5) series Cam-type color-coded panel mount inlets	(1) Set of (5) 16 Series Cam-type, color-coded panel mounts inlets	(1) set of (5) 16 series Cam-type color-coded panel mount inlets
Output	(6) NEMA 5-20, 20 amp, GFCI duplex receptacles	(6) 50 Amp, 3 Pole, 4 Wire, 120/240 VAC, California-style locking receptacles	(5) sets of (5) 16 vseries cam-type color-coded panel mount outlets
Agency Approval	N/A	N/A	N/A
Material	N/A	N/A	N/A
Feed Thru	none	none	none
Overcurrent protection	(12) v20 amp single pole branch-rates circuit breakers	(6) 50 amp 2 pole branch-rates circuit breakers	none
Width	14.5"	14.5"	11"
Length	14.5"	14.5"	20.5"
Height	13"	13"	18"
Weight	33 lbs	35 lbs	56 lbs

POWER DISTRIBUTION

NEMA 3R



400 AMP RENTAL DISTRIBUTION BOX

400 AMP RENTAL POWER INPUT PANEL

600 AMP RENTAL CONVERTIBLE ILINE PANEL

Manufacturer	Lex Products	Lex Products	TRYSSTAR
Model	PowerGATE 208V	PowerGATE 480V	ILine 600
AMPS	400	400	600
Rating	400 amp, 3 phase, 120/208 VAC, 60 hz, 4 pole, 5 wire	400 amp,v3 phase, 277/480 VAC, 60 hZ, 4 pole, 5 wire	no info on spec sheet
Enviromental Rating	Type 3R Rainproof	Type 3R Rainproof	NEMA 3R
Connector to Building Wiring	Lug terminals #2 AWG to 600MCM	Lug terminals #2 AWG to 600MCM	N/A
Input Connector	(5) series, 16 cam-type connectors in blue, black, red, white, and green	(5) series 16 camtype connectors in vbrow, orange, yellow, white, and green	N/A
Output	N/A	N/A	N/A
Agency Approval	UL Listed	UL Listed	UL Listed
Material	Fiberglass	Fiberglass	Powder Coated/ Stainless steel
Feed Thru	N/A	N/A	N/A
Overcurrent protection	N/A	N/A	N/A
Width	21"	21"	N/A
Length	10.5"	10.5"	N/A
Height	30.75"	30.75"	N/A
Weight	58 lbs	58 lbs	N/A

POWER DISTRIBUTION

NEMA 3R



600 AMP RENTAL ILINE PANEL



800 AMP RENTAL ILINE PANEL



1200 AMP RENTAL ILINE PANEL

Manufacturer	HIPOWER	TRYPSTAR	HIPOWER
Model	ILine 600	ILine 800	ILine 1200
AMPS	600	800	1200
Rating	600 amp, 3 phase, 600 VAC, 3 pole, 5 wire	no info on spec sheet	1200 amp, 3 phase, 600 VAC, 3 pale, 5 wire
Enviromental Rating	NEMA 3R	NEMA 3R	NEMA 3R
Connector to Building Wiring	N/A	N/A	N/A
Input Connector	male (2) series, 16 camlock in black, red, blue, white, green	N/A	male (4) seires, 16 camlock in black, red, blue, white, and green
Output	female (8) 400 amp	N/A	(6) 60 amp welder recapables plus (4) 400 amp camlock
Agency Approval	UL Listed	UL Listed	UL Listed
Material	Aluminum with Powder Coated Finish	Powder Coated/ Stainless steel	Aluminum with Powder Coated Finish
Feed Thru	N/A	N/A	N/A
Overcurrent protection	N/A	N/A	N/A
Width	42.5"	N/A	48"
Length	26.5"	N/A	40"
Height	50"	N/A	79"
Weight	340 lbs	N/A	750 lbs

TRANSFER SWITCHES

INDOOR/OUTDOOR

TAILORED FOR ANY INDUSTRY

Mobile Air & Power Rentals offers Automatic Transfer Switch (ATS) rentals available in many different size and configurations. Out switched are specifically set up for both indoor and outdoor use with Cam Lock input and output connections for safe and easy installation and removal. Generally, our transfer switches are used with emergency power generators to back up power from the utility source. This allows a safe switch from utility power to generator power, while maintaining isolation of each source from the other.



200 AMP RENTAL TRANSFER SWITCH



400 AMP RENTAL TRANSFER SWITCH

Manufacturer	ASCO Power Techonolgies	ASCO Power Techonolgies
Model	Series 300	Series 300
AMPS	200	400
Voltage	208/240V	277/480v
Enclosure Type	3R outdoor rated	3R outdoor rated
Primary Input Connection	Male Panel-Mount CamLock	Male Panel-Mount CamLock
Secondary Input Connection	Male Panel-Mount CamLock	Male Panel-Mount CamLock
Load Output Connection	Female Panel-Mount CamLock	Female Panel-Mount CamLock
Width	36.5"	36.5"
Length	16"	16"
Height	49.25"	49.25"
Weight	554 lbs	546 lbs

TRANSFER SWITCHES

INDOOR/OUTDOOR



800 AMP RENTAL TRANSFER SWITCH



3000 AMP RENTAL TRANSFER SWITCH

Manufacturer	Olympian	ASCO Power Technologies
Model	HTS System 800	Series 3000
AMPS	800	3000
Voltage	277/480V	600V
Enclosure Type	3R outdoor rated	3R outdoor rated
Primary Input Connection	Male Panel-Mount CamLock	Male Panel-Mount CamLock
Secondary Input Connection	Male Panel-Mount CamLock	Male Panel-Mount CamLock
Load Output Connection	Female Panel-Mount CamLock	Female Panel-Mount CamLock
Width	36"	41"
Length	36"	74"
Height	21"	95.5"
Weight	386 lbs	5,415 lbs

CABLES

TALK ABOUT RELIABILITY

JUST WHAT YOU NEED

Mobile Air & Power Rentals has cables that utilize the latest compounds for the right combination of durability and flexibility. We offer cable rentals as an add-on or alone to cater to your needs.



200 AMP RENTAL FEEDER CABLE TIE IN SET WITH CAMTYPE CONNECTORS - INDUSTRIAL



#4 AWG RENTAL CAM-TYPE FEMALE TAIL SET



100 AMP FEEDER CABLE EXTENTION WITH CAMTYPE CONNECTORS

Manufacturer	Lex Products	Lex Products	Lex Products
Cable	W (industrial)	SC extra hard usage cable	SC (Entertainment)
Temperature Rating	-58°-221°F	-58°-221°F	-58°-221°F
Industry Approvals	UL/MSHA Listed,RoHS compliant	UL/MSHA Listed,RoHS compliant	UL/MSHA Listed,RoHS compliant
Male Connector	Bare Cable End	16 Series Inline	16 Series Inline
Female Connector	(5) 16 Series Inline	16 Series Inline	16 Series Inline
NEMA Rating	Type 3R-weatherproof	Type 3R-weatherproof	Type 3R-weatherproof
Cable Gauge	2/0 AWG	#2 AWG	#2 AWG
Sleeve Material	Santoprene (TPE)	Santoprene (TPE)	Santoprene (TPE)

CABLES

TALK ABOUT RELIABILITY



**200 AMP RENTAL FEEDER CABLE TIE
IN SET WITH CAMTYPE CONNECTORS -
ENTERTAINMENT**



**400 AMP RENTAL FEEDER CABLE
EXTENSION WITH CAMTYPE CONNECTORS
- INDUSTRIAL**

Manufacturer	Lex Products or other	Lex Products or other
Cable	SC (entertainment)	W (industrial)
Temperature Rating	-58°-221°F	-58°-221°F
Industry Approvals	UL/MSHA Listed,RoHS compliant	nUL/MSHA Listed,RoHS complianta
Male Connector	Bare Cable End	16 Series Inline
Female Connector	(5) 16 Series Inline	16 Series Inline
NEMA Rating	Type 3R-weatherproof /	400 amp, 600 VAC
Cable Gauge	2/0 AWG	4/0 AWG
Sleeve Material	Santoprene (TPE)	Santoprene (TPE)

CONTACT US TODAY
FOR ALL YOUR HVAC &
POWER RENTAL NEEDS.



MOBILE
Air & Power Rentals

a division of Resolute Industrial

888.305.3038 | MOBILEAIR.COM